

# K1R142/1-A

surface-mounted luminaire • linear

*application* : office, healthcare, education, horeca, retail, leisure

*housing*: impact-resistant polycarbonate

*light source* : LED LP • 5000 K

*Lumen output in emergency mode* : 90 lm

*function*: single- and double-sided signage

*self test*: With extensive self-test EST+

*photobiological safety*: IEC/TR 62778: RG 0



## Mechanical properties

*dimensions* : 315 mm x 33 mm x 219 mm

*colour*: RAL9003-signalwhite

*ambient temperature*: from 5°C to 35°C •

## Battery

*mode of operation* : adjustable: non-maintained/maintained

*Battery*: 4 x NiMh 1,2V 1,1Ah

*autonomy* : \*90 minutes

## Luminance

*luminous flux* : 90 lm

*distance of perception* : 24

## Electrical properties

*power* : 2.8 W

*voltage*: 220-230V

*frequency* : 50-60Hz AC

*distance of perception* : 24

# K1R142/1-A

## Available accessories

K1RH0110 *recessed mounting frame*

K1RH0120 *right angle wall bracket*

K1RH0130 *adaptation plate for K5 renovation*

K1RH0140-0500 *suspension set, 0,5 m*

K1RH0140-1000 *suspension set, 1 m*

K1RH0140-2000 *suspension set, 2 m*

K1RH0170 *protective grille*

K1RH0190 *accessory for through wiring and/or surface mounted cabling*

K9RH5 *test button set*

## Dimensional drawing

