

K1R143/1-A

surface-mounted luminaire • linear

application : office, healthcare, education, horeca, retail, leisure

housing: impact-resistant polycarbonate

light source : LED LP • 5000 K

Lumen output in emergency mode : 90 lm

function: single- and double-sided signage

self test: With self test and wired control - ESM

photobiological safety: IEC/TR 62778: RG 0



Mechanical properties

dimensions : 315 mm x 33 mm x 219 mm

colour: RAL9003-signalwhite

ambient temperature: from 5°C to 35°C •

Battery

mode of operation : adjustable: non-maintained/maintained

Battery: 4 x NiMh 1,2V 1,1Ah

autonomy : *90 minutes

Luminance

luminous flux : 90 lm

distance of perception : 24

Electrical properties

power : 2.8 W

voltage: 220-230V

frequency : 50-60Hz AC

distance of perception : 24

K1R143/1-A

Available accessories

K1RH0110 *recessed mounting frame*

K1RH0120 *right angle wall bracket*

K1RH0130 *adaptation plate for K5 renovation*

K1RH0140-0500 *suspension set, 0,5 m*

K1RH0140-1000 *suspension set, 1 m*

K1RH0140-2000 *suspension set, 2 m*

K1RH0170 *protective grille*

K1RH0190 *accessory for through wiring and/or surface mounted cabling*

K9RH5 *test button set*

Dimensional drawing

