

# K1R213/3-A-D800A25

C0:C90 C0:D800 C90:A25

**recessed luminaire • round**

**application** : Office, Healthcare, Education, Horeca, Retail, Leisure

**light source** : high power LED • 5000 K

**optics** : lens • acrylic (PMMA)


**Lumen output in emergency mode** : 280 lm

**function**: escape route lighting

**monitoring**: ESM - wired /wireless

**photobiological safety**: EN 62471: RISK GROUP 1 UNLIMITED

ASNZ2293.1:2018 tested and compliant  
ETAP Testing #ETAP2020K1K1EM



## Product information

### Mechanical properties

**dimensions** : 110 mm x 70 mm

**cut-out size** : 85 mm x 70 mm

**colour**: RAL9003-signalwhite

**IP**: IP42

**IK**: IK04

**ambient temperature**: from 5°C to 35°C •

### Battery

**mode of operation** : adjustable: non-maintained/maintained

**Battery**: 4 x NiMh 1,2V 2,2Ah

**autonomy** : \*90 minutes

### Electrical properties


**power** : 0.9 W

**voltage**: 220-230V


**frequency** : 50-60Hz AC

Luminance

luminous flux : 280 lm



Distance tables: ceiling mounted



ER Ceiling for 1.0 Lux and 280 lm

H (m)	a	b	c	d
2.6	9.0	19.5	1.9	4.3
2.8	9.5	20.7	2.0	4.5
3.0	10.0	21.8	2.1	4.6
3.5	11.1	24.5	2.4	5.2
4.0	12.0	27.1	2.7	5.9
4.5	12.9	29.5	2.9	6.5
5.0	13.7	31.6	3.0	7.0
6.0	11.2	35.3	2.2	7.4
7.0	9.6	35.1	1.6	7.0
8.0	7.0	35.2	1.2	7.2
10.0	---	26.4	0.7	4.3

## Available accessories

K9RH88X1 *Adaptation plate for K5 renovation (RAL9003)*

---


K9RH88X2 *Adaptation plate for K5 renovation (RAL9006)*

---

K9RH5 *Test button set*

---

Dimensional drawing



Min.150 mm

